ORDINANCE NO. 2005-2

AN ORDINANCE OF THE TOWNSHIP OF GREENWICH, COUNTY OF BERKS AND COMMONWEALTH OF PENNSYLVANIA, REVISING THE GREENWICH TOWNSHIP SUBDIVISION AND LAND DEVELOPMENT ORDINANCE OF 1996, AS AMENDED, TO REVISE SECTIONS 602.2 CARTWAY PAVING, 602.3 CURBS, 602.4 SIDEWALKS, TO PROVIDE CONSTRUCTION STANDARDS FOR THE SAME.

BE IT ORDAINED and ENACTED by the Board of Supervisors of Greenwich Township, Berks County, Pennsylvania, and it is hereby ordained and enacted by the authority of the same as follows:

SECTION 1. The Greenwich Township Subdivision Regulations of 1996, as amended, is hereby revised to provide the following revisions:

- 602.2 <u>Cartway Paving</u>: All streets shall be paved to full cartway width (as shown on the Final Plan) and as required by Section 502.3 of this Ordinance, as more fully described in Construction Standard attached as Appendices A and D to Subdivision Ordinance.
- of all streets, except along service streets in accordance with Township Ordinances. Curbs shall be either the vertical type, or rolled curb-and-gutter type, except that rolled curbs shall not be used on streets whose grade exceeds six (6) percent, or on any collector or major streets. The transition from one type of curb to another shall be made only at a street intersection. Adequate provision shall be made for driveway entrances. Construction of

ORWIG LAW OFFICES

A PROFESSIONAL CORPORATION

1940 N. 13th Street

1940 N. 13th Street Suite 215 Reading, PA 19604

(610) 939-9866

said curbs to conform to Construction Standard attached as Appendix B to Subdivision Ordinance.

602.4 Sidewalks:

- (a) Sidewalks shall be a minimum width of four (4) feet and shall be installed on both sides of all street except that no sidewalks shall be required along service streets and where required, sidewalks shall be installed on only one (1) side of marginal access streets.
- (b) All sidewalks, curbs and gutters shall be installed in accordance with these regulations and with Township curb, gutter and sidewalk Ordinance, as more fully described in Construction Standard attached as Appendix C to Subdivision Ordinance.
- ${\tt SECTION~2}.$ The aforementioned referenced Appendices A, B, C and D are attached hereto and made a part hereof as follows:
- SECTION 3. All other provisions and regulations as contained in the Greenwich Township Subdivision and Land Development Ordinance of 1996, as amended, which have not been revised or amended by this Ordinance shall remain in full force and effect.
- SECTION 4. All ordinances or parts of ordinances inconsistent with the provisions of this Ordinance are hereby repealed insofar, but only insofar, as the same are inconsistent herewith.
 - SECTION 5. The provisions of this Ordinance are severable

ORWIG LAW OFFICES

A PROFESSIONAL CORPORATION

1940 N. 13th Street Suite 215 Reading, PA 19604

(610) 939-9866

and if any provision or part thereof shall be held invalid, unconstitutional or inapplicable to any person or circumstances, such invalidity, unconstitutionality or inapplicability shall not effect or impair the remaining provisions or parts thereof, of this Ordinance.

<u>SECTION 6</u>. This Ordinance Shall take effect five (5) days subsequent to its passage.

ORDAINED AND ENACTED by the Board of Supervisors of Greenwich Township, Berks County, Pennsylvania, in lawful session duly assembled, this 7^{7} day of 800.

BOARD OF SUPERVISORS OF GREENWICH TOWNSHIP, BERKS COUNTY, PA

Victor M. Berger Chairman

Oscar Kleinsmith, Supervisor

Laurie Baker, Supervisor

Attest:

Township Secretary


ATTORNEYS AT LAW

ORWIG LAW OFFICES

1940 N. 13th Street Suite 215 Reading, PA 19604


(610) 939-9866

CURB CONSTRUCTION STANDARDS BERKS COUNTY, PENNSYLVANIA GREENWICH TOWNSHIP



CURB CUT FOR DRIVEWAY ENTRANCE

No Scale



STANDARD CURB DETAIL

No Scale

NOTES:

1. All curb shall be constructed on a minimum of 4" of AASHTO #57 stone.

2. Expansion joints shall consist of 1/2" thick preformed, nonextruding and resilient joint filler and shall be placed at 20—foot intervals to the full depth of fixed—form curb. Expansion joints shall be placed at 80—foot intervals for slipformed curb.


slipformed curb.

3. Slipformed curb shall be sawcut to the street surface at 10—foot intervals. All fixed form curb shall be scored at 10—foot intervals.

4. Concrete mix shall achieve a minimum 28—day strength of 3500 psi with 6% air entrainment.

TEI 7/98 Last Revised 10/04/2005

GREENWICH TOWNSHIP BERKS COUNTY, PENNSYLVANIA SIDEWALK CONSTRUCTION STANDARDS




TYPICAL SIDEWALK CROSS SECTION

No Scale

TEI 7/98

Last Revised 10/17/03

ROAD RECONSTRUCTION/WIDENING STANDARDS BERKS COUNTY, PENNSYLVANIA GREENWICH TOWNSHIP



TYPICAL ROAD CROSS SECTION

Scale

Last Revised 4/5/05

TEI 10/03

ATTACHMENT D